

Research Article

Assessing the Operation Management: A Case of Narayani Lift Irrigation System, Nepal

Ashish Ruwali¹, Rajib Ghimire¹, Sagar Nepal¹, Shasit Gautam¹, Subin KC¹, Sudip Dhakal¹, Sandeep Parajuli², AK Mishra³

¹Students, ²Assistant Professor, Department of Civil Engineering, Oxford College of Engineering and Management, Gaidakot-02, Nawalpur, Nepal.

³Associate Professor, Madan Bhandari Memorial Academy Nepal, Urlabari, Morang, Nepal.

DOI:<https://doi.org/10.24321/2455.3190.202201>

I N F O

Corresponding Author:

AK Mishra, Associate Professor, Madan Bhandari Memorial Academy Nepal, Urlabari, Morang, Nepal.

E-mail Id:

anjaymishra2000@gmail.com

Orcid Id:

<http://orcid.org/0000-0003-2803-4918>

How to cite this article:

Ruwali A, Ghimire R, Nepal S et al. Assessing the Operation Management: A Case of Narayani Lift Irrigation System, Nepal. *J Adv Res Geo Sci Rem Sens* 2022; 9(3&4): 1-25.

Date of Submission: 2022-08-05

Date of Acceptance: 2022-10-03

A B S T R A C T

Narayani Lift Irrigation System is one of the oldest lift irrigation systems in Nepal, constructed in 1982. The machines used are as old as the project and, some were maintained and are still in operation. The study focuses on the operation assessment of the Narayani Lift Irrigation System. Field visits with a checklist, a Questionnaire survey, Key informant interviews were the main methods of data collection. The data was analysed using the Relative Importance Index and descriptive statistics.

The past performance of the system indicates irrigation coverage of only 4,700 Ha of the pump scheme that too with occasional supplements to the Khageri irrigation system in the event of scarcity. Dispute during the water distribution time was frequently observed and the role of NLIWUA was effective in dispute management.

The system operation changes were observed in the socio-economic and agricultural status of the users. An increase in the economic status by 45% is noted, 55.4 % of farmers have been motivated towards agriculture. A shift of farmers from rice plantations to cash crops is noted. The operational cost and maintenance cost of components of the pump house were allocated by Government. The budget allocated was sufficient only for the temporary maintenance, but the system needs proper rehabilitation. Sediment Management is the main problem of the system; hence improvement needs to be done.

Keywords: Disputes, Distribution, Availability, Sediment, Budget, WUA

Introduction

Narayani Lift Irrigation System (NLIS) is amongst those irrigation systems which provide irrigation to the upper terraces of the Narayani River of the Bharatpur Metropolitan City. This system was initially constructed in 1982 as Chitwan Valley Development Project (CVDP) by the Department of Irrigation, which included three

irrigation schemes Panchakanya, Lothar and Narayani Lift. The Narayani Lift Irrigation Project (NLIP) was studied and designed by a German Consulting Firm "Agra and Hydro Technique GMBH" in 1972 to pump water from the Narayani river and irrigate 4,700 Ha of land. The project also supplemented the Khageri Irrigation System having a command area of 3,900 Ha. The project was commissioned

in 1982 and was operational as NLIS. The NLIS has two staged pumps and two canal systems: canal-B and canal-C. Pump-A lifts water from the river to the 20 m high link canal and can pump up to 17 m³/s, while pump-B lifts water from the link canal to 18 m to canal-C and can pump up to 7.2 m³/s. (Narayani Lift, 2021).

The link canal, which joins pump house-A and B is 500 m in length. The main canal B is separated into two branches just upstream of pump house-B. The pump house-B lifts water to canal C. The canal-B system irrigates 2,400 ha of land in the middle terrace through a 19.50 km long main canal and 9 branch canals. The canal-C system irrigates 2,300 ha of land on the upper terrace through a 16.50 km long main canal and 7 branch canals. The system was developed up to the command area level with tertiary canals to serve an irrigation block of about 100 ha. (MOE,2076).

The past performance of the system indicates irrigation coverage of only 4,700 ha of the pump scheme only with occasional supplements to the Khageri irrigation system in the event of scarcity. The system was broken down from 1992 to 1994, rehabilitation works were carried out for the pumps in "A" and resumed operation since then. The system is operating with difficulty as frequent breaks down of the electrical and mechanical parts occur. In addition, there are various deficiencies in the electro-mechanical equipment, also problems of sediment influx into the canal system. The system is hardly operational during the rainy season only for the paddy crops when the sediment content in the river water is high. The pumps are unable to operate during low flow in the winter and spring season. (Development, M. o. (2075/2076): Mishra, A. K., & Aithal, P. S., 2022)

Objective of the Study

The objective of the study is to analyse the Waters Users Management and operation mechanism of distribution of water in the Narayani lift irrigation system.

Literature Review

a little introduction about what this section talk about and then you can demonstrate the sub titles.

Climate and Agro-Ecology

Climatic condition recorded in the year 2020 in Chitwan (station- Rampur at 256m) district is shown in Table 1.

Table 1. Climatic Condition

| Year | Air Temperature °C | | | Absolute Extreme | | Relative Humidity % | | Precipitation mm | | No. of Rainy Days |
|------|--------------------|------|-------|------------------|-------------|---------------------|-------|------------------|------------------------|-------------------|
| | Max | Min | Daily | Max / Month | Min / Month | Observed at (NST) | | Total | Max in 24 hrs. / Month | 1:00 |
| | | | | | | 08:45 | 17:45 | | | |
| 2007 | 30.7 | 18.3 | 24.5 | 40/May | 4.2/Jan | 87 | 74 | 2743 | 155/Sept | 112 |

Source: Department of Hydrology and Metrology

Topography, Land use, Drainage

The altitude of the Chitwan district varies from 144 m to 1947 m from the mean sea level (MSL). It has spread over 221800 acres of land. Out of total acres of land, (46894 -21.14%), (18822 -8.49%), (142422 - 64.21%) and (13652 - 6.16%) of land are occupied by agricultural, pasture, forest and others (steep land, river, cliff, road etc.) respectively. (Metrology, D. o. (2075): District Development Committee. (2072): Rijal, E., Khatri, E., & Kharel, E. (2018). The land use pattern is shown in Table 2.

Table 2. Land Use Pattern

| S. No. | Physiographic Distribution of Land | Unit | Area | Percentage by Weightage of Total |
|--------|---|------|--------|--|
| | Total Area of the District | Ha | 221800 | 100.00 |
| | Cultivable Land | Ha | 46894 | 21.14 |
| | Cultivated Land | Ha | 44291 | 19.97 94.45 (of cultivable land) |
| | Non Cultivated Land | Ha | 2553 | 1.15 5.44 (of cultivable land) |
| | Grazing Land | Ha | 18822 | 8.49 |
| | Forest | Ha | 142422 | 64.21 |
| | Others (Land slide, River/ Drainage, high slope, Rock, Road, Settlement etc.) | Ha | 13652 | 6.16 |

Source: District Profile DDC Chitwan 2010: Gajurel, K., & K.C., T. B. (2003).

Surface Water Resources

Major surface water resources are Narayani , Rapti, Lothar, Kayar Khola, Rigdi, Khageri, Reeu rivers, Satrahajar, Bishajar, Atthais Hajar, Muntha, Devi, Lami, Tamor Ghaila, Kasara, Nanda-Bhauju, Anjura, Manjura, Gaduwa, Anjana, Parsuram Kunda, Baikuntha Lakes.

Existing Irrigation Practices

Narayani, Rapti, Lothar, Kayar, Rigdi and Rieu rivers are the main existing sources of irrigation in the area. Big irrigation canals, deep tube wells, shallow tube wells, cooperative irrigation schemes, private water pumping and wells are the existing irrigation practice in the Chitwan district (Gajurel, K, & KC, TB. (2003).). According to the DDC Chitwan profile, 44291-acre land had been utilized for agriculture purposes in the Chitwan district. Out of a total, 29499-acre lands have irrigation facilities, out of which only 15885-acre land have irrigation facilities for the whole year and 14958-acre land have partial (seasonal) irrigation facilities. About 14448-acre land have no irrigation facility. (Mishra, A. K. (2022): Dahal AK, Mishra AK, & Aithal PS. (2022): Dahal AK, Mishra AK, & Aithal PS. (2022): Mishra AK, & Dahal AK (2022).

Irrigation from Lift System

According to the annual agriculture development and statistical book, only the Narayani lift irrigation system in the Chitwan district is the main working system. It has been serving about 4700 Ha land of Bharatpur Metropolitan city.

Irrigation from Other Sources

About 15885 Ha of land was irrigated from different types/

sources of perennial irrigation systems within the district. Out of that, from east Rapti, Khagari, Panchkanya, Pithuwa irrigation canal systems 7383 Ha; Deep tube wells 374 Ha; Sallow tube wells 1704 Ha, small irrigation schemes 5545 Ha, Co-operative irrigation schemes 606 Ha and others/private pump sets/dug wells 273 Ha lands irrigated existed (Singh, M., Liebrand, J., & Joshi, D. (2014)): Acharya, M., Poudel, R., & Bhandari, B. (1993/94): APROSC, & JMA. (1995). The details of the irrigation system are presented below in Table 3.

Socio-Economic Situation

Social Overview

As per the population census, 2001, the total population of the district is 472084 attributing to 92863. The 2010's projection shows that the total number of households in the district is 119691. Out of the total population, the composition of males and females are 235084 and 304774 respectively with a sex ratio of 99. Acharya, M., Poudel, R., & Bhandari, B. (1993/94): Bhatta, K. P., Sharma, R., & Ishida, A. (2005): Pradhan, P. (2000). The average household size is 5.08. The density of the population is 213 km² (2010 projection- 275). The details of project-related municipality and VDCs population are presented in Table 4.

Table 3. Details of Existing Irrigation System and it's Coverage

| Project Name | Location | Command area (Ha) | Covered area |
|---|---|-------------------|--------------|
| Kageri Irrigation System | Kalika Municipality, Ratnanagar Municipality Bharatpur Metropolitan city(West chitwan) | 3900 | 5000 |
| Narayani Lift Irrigation System | Bharatpur Metropolitan City | 4700 | 4700 |
| Panchakanya Irrigation System | Ratnanagar Municipality | 600 | 1200 |
| Ghangar Irrigation System | Madi Municipality | 134 | 168 |
| Khaire Khola Irrigation Project | Madi Municipality | 35 | 45 |
| Dehitar Irrigation Project | Rapti Municipality (Lothar) | 25 | 30 |
| Yangkrang Irrigation Project | Icchyakamana Rural Municipality | 30 | 35 |
| Chandra Khola Irrigation Project | Madi Municipality | 45 | 65 |
| Reoi Bagai Irrigation Project | Madi Municipality | 110 | 185 |
| Parut Khola Irrigation Project | Madi Municipality | 93 | 158 |
| Lagaura Parsa Irrigation Project | Bharatpur Metropolitan City | 102 | 172 |
| Ganganagar Irrigation Project | Bharatpur Metropolitan City | 250 | 300 |
| Maroth Khola Irrigation Project | Madi Municipality | 300 | 450 |
| Ajanantatal Irrigation Project | Bharatpur Metropolitan City | 550 | 690 |
| Patihani Parsa Irrigation Project | Bharatpur Metropolitan City | 665 | 1050 |
| Uppalo Reoi Irrigation Project | Madi Municipality | 100 | 225 |
| Gopalnagar/Harinagar/Gaurinagar/ Irrigation Project | Madi Municipality | 162 | 327 |
| Lothar Irrigation System | Rapti Municipality | 1000 | 1600 |

| | | | |
|---|---|-------|-------|
| Purbi Rapti Irrigation Project (90 canal) | Rapti Municipality, Khairahani Municipality | 10235 | 24387 |
| Different 25 Irrigation Projects | | 825 | 1250 |
| Ground Irrigation Project | | 678 | |
| Total | | 24539 | 42037 |

Source: District Profile DDC Chitwan 2010: Gajurel, K., & K.C., T. B. (2003)

Table 4. Distribution of Households and Population and Family Size

| S.No | Name of VDCs & Municipality | 2001 Census | | | | | 2010 Projection | | | |
|-------|-----------------------------|--------------|-----------------|------------------|-------|--------|-----------------|------------------|-------|--------|
| | | AVG H/H Size | Total no of HHs | Total Population | Male | Female | Total no of HHs | Total Population | Male | Female |
| 1 | Bharatpur N.P | 4.48 | 19922 | 89323 | 45858 | 43465 | 24677 | 115128 | 59106 | 56022 |
| 2 | Fulbari VDC | 5.08 | 674 | 3426 | 1696 | 1730 | 869 | 4416 | 2186 | 2230 |
| 3 | Gitanagar | 4.75 | 2550 | 12106 | 5888 | 6218 | 3287 | 15603 | 7589 | 8014 |
| 4 | Mangalpur | 4.92 | 2951 | 14508 | 7126 | 7382 | 3804 | 18699 | 9185 | 9515 |
| 5 | Saradanagar | 4.83 | 1983 | 9584 | 4587 | 4997 | 2556 | 12353 | 5912 | 6441 |
| 6 | Shivanagar | 4.8 | 1436 | 6891 | 3369 | 3522 | 1851 | 8882 | 4342 | 4540 |
| Total | | 4.60 | 29516 | 135838 | 68524 | 67314 | 37044 | 175081 | 88320 | 86762 |

Source: CBS, 2011

The main market centre of the area are Narayangad, Mungling, Bharatpur, Ratnanagar & Other market centres are Parsadhap, Rampur, Jagatpur, Shivanagar, Bhandara, Kuringhat, Basantapur (Madi), Bandarjhula, Parbatipur, Meghauri, Chanauli, Mangalpur, Gitanagar, Parsa (Khairahani), Gardi (Madi), Kalyanpur (Madi), Patihani, Saradanagar. (Statistical Year Book of Nepal. (2003): Sharma K R (1996) Singh M, Liebrand J, & Joshi D. (2014).

Economic Activities

As per CBS, 2001, about 57.51% of all persons were engaged in economic activities, while the remaining 42.49% were taking care of the household, student, retired or economically inactive for other reasons. The data is mentioned in Table 5.

Approximately, the highest 45.04% of the economic active population was involved in farm fishing/ forestry works. About 13.76% were engaged as service workers and shop, market sales workers (CBS,2011). The category of workers accounted for 11.51% engaged as craft and trade workers. About 6.33% were found professional/ semi-professional/ technical workers. 2.98% depend upon

administrative and clerical work. About 2.78% of people were engaged in production labour worker. 0.91% and 16.68% economically active people were found engaged in legislators/ senior officials/ manager and other and not stated works respectively.

Methodology

Study Process

In order to meet objectives of the study, different literatures related to Narayani Lift Irrigation System, social parameter, climatic condition, irrigation and agricultural condition of command area as well as whole district, water demand in these area, Plans, policies, rules and regulations related to the irrigation, user committee, water resource use in context of Nepal have been collected and studied, which provided the secondary data relevant to this study. After the collection of the information and data required for the case study, field survey is done around the command area and office to study the present operating condition and maintenance status of the system. Also interview is done with governmental officers, members of user committee and local farmers to obtain ground reality of system and

Table 5. Economically Active and Inactive Male Female Population

| Status | 2001 Census | | | 2010 Projection | | |
|-----------------------|--------------------|--------------------|-------------------|--------------------|--------------------|--------------------|
| | Total | Male | Female | Total | Male | Female |
| Economically Active | 208515 (57.51%) | 119723 (66.81%) | 88792 (48.42%) | 268755 (57.51%) | 154311 (66.81%) | 114444 (48.42%) |
| Economically Inactive | 154059 (42.49%) | 59489 (33.19%) | 94570 (51.58%) | 198566 (42.49%) | 76675 (33.19%) | 121891 (51.58%) |
| Total | 362574 | 179212 | 183362 | 467321 | 230986 | 236335 |

obtain a brief of role of user committee. On the collection of both primary and secondary data, a comprehensive analysis was done. Post analysis, the different dimensions and alternative ways for the solutions had been identified. The whole process of the methodology for this study is schematically demonstrated through Figure 1.

Study Area

Chitwan is amongst those districts of the Narayani zone that lie in the Central Development Region of Nepal. It covers an area of 2218 square kilometres. It has extended between $27^{\circ} 15' - 27^{\circ} 45'$ N latitudes and $84^{\circ} 27' - 85^{\circ} 85'$ E longitudes. It covers altogether 1 Rural Municipality-Icchyaamana Rural Municipality, 1 metropolitan city-Bharatpur and 4 municipalities – Ratnanagar, Khaireni, Rapti, Madi. Narayani Lift Irrigation system has been serving about 4700 Ha land of Bharatpur Metropolitan City (Narayani Lift (2021): Gajurel K, & KC, TB (2003)) About 15,885 Ha of land has been irrigated from different types/ sources of perennial irrigation systems within the district (Gajurel K, KC, TB (2003)). The map below shows the topography and the command area of the Narayani Lift Irrigation System (Figure 2).

27'-85° 85' E longitudes. It covers altogether 1 Rural Municipality-Icchyaamana Rural Municipality, 1 metropolitan city-Bharatpur and 4 municipalities – Ratnanagar, Khaireni, Rapti, Madi. Narayani Lift Irrigation system has been serving about 4700 Ha land of Bharatpur Metropolitan City (Narayani Lift (2021): Gajurel K, & KC, TB (2003)) About 15,885 Ha of land has been irrigated from different types/ sources of perennial irrigation systems within the district (Gajurel K, KC, TB (2003)). The map below shows the topography and the command area of the Narayani Lift Irrigation System (Figure 2).




Figure 1.General Methodology




Figure 2.Topographic Map of Narayani lift Irrigation Project

Source: Department of Survey, Government of Nepal

Population Selection and Sampling

Respondents from diverse backgrounds were selected. The respondents would be governmental officials of the Narayani Lift Irrigation System, members of the user committee responsible for the overall management of the system and local farmers using the service. The distribution of the respondent is shown in Table 6.

Table 6. Respondents of Primary Data for the Questionnaire Survey

| S.No | Category of Respondents | Number | Percentage |
|------|--------------------------|--------|------------|
| 1 | Government officials | 5 | 8.33 |
| 2 | Member of user committee | 15 | 25 |
| 3 | Local farmers | 40 | 66.67 |
| | Total | 60 | 100 |

Data Analysis

Data analysis was been done at different stages using statistical tools and the data is presented in tables and tools like bar charts and pie-chart.

Relative Importance Index

The hierarchy of the causes of disputes and problems and threats of the system were identified using the Relative Importance Index (RII). The participating respondents have provided numerical scoring expressing their opinions on the degree of importance of each Indicator. The collected data was analyzed using various statistical methods.

$$RII = \frac{\sum_{i=1}^n \frac{W_i}{X_i} \times \text{Average Importance}}{5} \times 100\% \text{ (Mishra, A.K., 2019)}$$

Where,

W_i = the weight given to the i th response: $i=1, 2, 3, 4, 5$,

X_i = frequency of the i th response,

A = the highest weight (5 in this study),

n = the number of respondents.

Analytical Research

The descriptive research was also carried out, the analytical research was mainly focused on the first objectives of the study. The analytical research was helpful to find out the opinion of farmers, member of WUA and governmental officials about the system and also to find whether the roles of WUA was effective and the opinion of farmers and government officials about WUA. An analytical questionnaire survey was done (Mishra, Anjay Kumar, Prakash Yadav, & Aithal, P. S., (2021)).

Result and Discussion

Source and Supply

The source of the irrigation system is the Narayani River

located at the Narayanghat, Chitwan district, the irrigation water directly intakes from the Narayani River through the gabion wall constructed on the left bank without weirs. Because of the seasonal fluctuation of the water level, a range of five meters ordinarily (average minimum water height of 92.5 m and maximum 98.0 m), pipe inlets with four different elevations were installed on the wall. During monsoon, the lower inlet pipes were closed by a gate and the surface water is intake through the upper ones.

In 2020 water pumping scenario is $7 \text{ m}^3/\text{s}$ water lift from pump house A is distributed $6.2 \text{ m}^3/\text{s}$ to canal B system and $0.8 \text{ m}^3/\text{s}$ to canal C system. Irrigation peak water demand of canal B system for remaining agricultural command area for agriculture 2267.90 ha with peak period crop water requirement $2.0 \text{ ltr}/\text{sec}/\text{ha}$ is $4.54 \text{ m}^3/\text{sec}$. Similarly irrigation peak water demand of Canal C system for remaining command area for agriculture 945 ha with peak period crop water requirement $2.0 \text{ ltr}/\text{sec}/\text{ha}$ is $1.89 \text{ m}^3/\text{sec}$.

Source of Irrigation Water Before NLIS

Irrigation has been done in Chitwan as inhabitants increased with the migration of people from different districts. The location of Chitwan in Terai is considered the bread basket of Nepal. Around the command area, the traditional source of irrigation such as groundwater, rainwater and surface water was used, also groundwater source such as tube well was commonly found. The result of the survey on the source of irrigation when the Narayani Lift Irrigation System is not operating shows that the majority of farmers i.e 55% in the command area are dependent on groundwater sources such as tube wells and Bore well. During the survey also many bore wells were seen and in every house, there was a tube well in the command area.

Around 25% of farmers wait for rainwater for irrigation. Generally, those farmers who have cultivable land far from residents such people are found to depend on rainwater and 20% of them used surface water from nearby lakes during the monsoon when lakes got flooded.

Water Availability Status

NLIS withdraw water from snow feed perennial Narayani river. Narayani River flows throughout the year and during monsoon season high intensity discharge is recorded. Only during the monsoon season water enters the intake of the system and feed the system. Generally, the system is operated in July and feeds the canal for up to 3-5 months. The water from the source operated only for some months may not be abundant. On asked sufficiency status of water in the system to local farmers and water user, association members result obtained is illustrated in Figure 3.

Farmers and members of the water user association have somewhat similar thoughts on the sufficiency of water. Both completely deny that water from the source is fully

sufficient for irrigation, 20% of them find water partially sufficient and in the same context, 46.67% of the members of the water user association agree. The majority of farmers' i.e 57.5% agrees that water from the system is sufficient for one crop season and 40% of the member of the water user association agree with this context. It is found that 22.5% of the farmer and 13.33% of the members of the user association accept that water is not sufficient for irrigation.

Since the majority of the beneficiaries of the system agrees on partial sufficiency of water and used only for one crop season, also water is fed in intake of the system only during monsoon study team thought to study for the necessity of secondary source for sufficient intake of water and result is presented in Figure 4.

All stakeholders i.e local farmers, member of WUA and government officials strongly disagree with denying of necessity of secondary sources for intake of water in the system and also, 52.5% of farmers, 40% of the member of WUA and 60% of government officials suggest it is most necessary of a secondary source to increase the abundance of water in the system.

Pumping Stations

Two pumping stations are Pump station "A" constructed at the intake point and "B" which is 500 m upstream of the "A" station connected with the Link canal. The pumps are vertical turbine flow type of Indian made. The capacity of Pump station "A" is shown in Table 4 and of Pump station, "B" is shown in Table 7.




Figure 3. Sufficiency status of water in system




Figure 4. Necessity of Secondary Source for Sufficient Intake of Water in System

Table 7. Pump Installed at Pump House “A”

| Discharge (m ³ /sec) | Capacity | Number | Remarks |
|---------------------------------|----------|--------|---|
| 4.00 m ³ /sec | 1200 KW | 2 Nos | Both pumps are operated with frequent maintenance |
| 2.00 m ³ /sec | 750 KW | 2 Nos | Both pumps are operated with frequent maintenance |
| 1.00 m ³ /sec | 330 KW | 1 Nos. | Damaged/motor winding was burst. |
| Total Nos. | | 5.00 | |

Table 8. Pump Installed at Pump House “B”

| Discharge (m ³ /sec) | Capacity | Number | Remarks |
|---------------------------------|----------|--------|--|
| 1.6 m ³ /sec | 500 KW | 1 Nos | Motor winding is burst |
| 0.8 m ³ /sec | 250 KW | 3 Nos. | 2 nos. pumps are operated with frequent maintenance where as one pump is not working completely. |
| Total Nos. | | 4.00 | |

Of the 5 motors installed at Pump House “A”, one motor of 330 kW capacity is damaged completely and the remaining 4 motors (2 motors of 1200 kW and 2 motors of 750 kW) are operated with frequent maintenance. Every after the pump operation, maintenance of the pump is been done for the operation of the pump for next year.

There are a total of 4 pumps installed at Pump House “B”, of which motor winding of one motor of 500 kW capacity is completely burst, of 3 pumps of 250 kW, 1 pump is completely not working and 2 pumps are operated with frequent maintenance.

Link Canal

The distance of 500 m length (Lining Canal) links the pump stations “A” and “B” with 1/10,000 of canal slope, 3.5m of bottom width, 3.3m of depth and 1:1.1 of canal inside slope. Silt deposit on the bed of canal up to the 1m depth while surveying.

Distribution System

Canal “B” System

Main Canal

Main Canal “B” is diverted from the link canal and jointed the Khageri Canal at the end in order to supply excess water to Khageri System. It is 17.6 km of wet masonry lining canal with a conveyance capacity of 7.8 m³/s and average slope of 1/ 6,500, located middle elevation area between Main Canal “C” and Khageri Canal. Division weirs are installed on main canal at some divergent points to secondary, slide gates are constructed at the beginning point of secondary canals. These gates are operated by the project staff, but there is no check and water measurement structures.

Secondary Canals

There are nine secondary canals and the total length is 15.5 km with the same lining structure as main canal.

Tertiary Canals

Tertiaries are earth canals with brick masonry lining at the inlet points. Round-shaped sluice gates are installed at the point’s directory to intake water from the main canal to the tertiary. From secondary canals, the round-shaped slice gates and stop logs are located at the inlet of tertiaries. Drop structures are mainly made of stone masonry and some part of brick masonry. Main Canal “B” is not damaged so much, but soil sedimentation is observed all along the canal and it reduces the canal’s water conveying capacity. After the monsoon season, huge amount of settled soil was removed from the canal.

Canal “C” System

Main Canal

Main Canal “C” is 10.2 km of wet masonry lining canal after the pump station “B”, flowing from north to south on the border of the project area and Mahendra Reserved Forest; the area with high elevation in the project area. Division structures are in the same condition as the “B” system.

Secondary Canals

There are six secondary canals of 20.5 km total length, also have no check and water measurement structures.

Tertiary Canals

There are 52 tertiaries of 61.5 km in total length, the structures are the same as the “B” system. The soil sedimentation is only observed from the beginning point up to the duckbill weir of 771 m points.



Figure 5



Figure 6

In most of the lower parts the soil is not settled, because of the high flow velocity, the canal is eroded and broken at many points. From this part, considerable water is leaked to the ponds in the reserved forest.

The canal "B" system contains two secondary canals No. 2 (BL2) and No. 6 (BL6). "C" system consists of Major canal CL1, which in the preset state is not functioning and most of its stretches are encroached, choked and filled. The majority length of the canal passes through the urban area

other secondary canals CL-2, CL-3, CL-4, CL-5, CL-6 are the branch of CL-1 hence all are not functioning. Whereas, CL-7 secondary canal lies at Gauriganj has still important for its command area useful for farming, but this area has a deficit of the irrigation water.

Farm/ Service Road

A total length of 150 km was constructed as farm road and service road for canal maintenance, which has some 3 m width and gravel pavement.

Main Canal Structures

Main Canal “B” is 17.681 km out of which a total of 2.5 km is masonry lining separated at different places and the rest are wet masonry lining canals with a conveyance capacity of 7.8 m³/ sec and an average slope of 1/6,500, located in middle elevation area between Main Canal “C” and Khageri Canal. Division weirs are installed on the main canal at some divergent points to the secondary, slide gates are constructed at the beginning point of secondary canals. These gates are operated by the project staff, but there are no check and water measurement structures.

Main Canal “C” starts from the 165 m of long at the beginning from pump house “B” is underground with HDP main pressure pipe and 10.2 km open canal out of which

total 3.5 km lining separated at different places of wet masonry lining canal after the pump station “B”, flowing from north to south on the border of the project area and Reserved Forest; the area with high elevation in the project area. Division structures are in the same condition as in the “B” system.

Command Area

NLIS was designed and operated to irrigate 4,700 Ha of land. The project was also made operational to supplement the Khageri Irrigation System having a command area of 3,900 Ha. The total area under the NLIS designed irrigation is found to be reduced from 2488.90 to 2267.90 Ha among canal “B” and 2262.35 to 944.075 Ha in the “C” system. The land use plan of the project for study year i.e 2020 is shown in Table 9.

Table 9. Land Use Plan of Project

| S. No. | | Tertiary Canal | Area (Ha) | | | Canal Link |
|--------|----------------|----------------|-----------|-----------|-------------|------------|
| | | | Total | Irrigated | Unirrigated | |
| 1 | i | B1-T1 | 32.50 | 32.50 | 0.00 | B |
| | ii | BL1 | 71.60 | 35.30 | 36.30 | B |
| | iii | B1-T2 | 8.40 | 6.20 | 2.20 | BL2 |
| | iv | B1-T3 | 27.60 | 22.60 | 5.00 | BL2 |
| | v | B1-T4 | 17.80 | 15.80 | 2.00 | BL2 |
| | vi | B1-T5 | 10.10 | 0.00 | 10.10 | BL1 |
| | Sub-total "B1" | 168.00 | 112.40 | 55.60 | | BL2 |
| 2 | i | B2-T1 | 10.60 | 5.70 | 4.90 | BL2 |
| | ii | B2-T2 | 17.10 | 13.00 | 4.10 | BL2 |
| | iii | B2-T3 | 17.40 | 17.40 | 0.00 | BL2 |
| | iv | B2-T4 | 57.30 | 44.90 | 12.40 | BL2 |
| | v | B2-T5 | 17.10 | 7.80 | 9.30 | BL2 |
| | vi | B2-T6 | 21.00 | 12.60 | 8.40 | BL2 |
| | vii | B2-T7 | 21.40 | 7.20 | 14.20 | BL2 |
| | Sub-total "B2" | 161.90 | 108.60 | 53.30 | | |
| 3 | i | B3-T1 | 25.80 | 23.40 | 2.40 | BL2 |
| | ii | B3-T2 | 15.00 | 8.00 | 7.00 | BL2 |
| | iii | B3-T3 | 52.80 | 11.90 | 40.90 | BL2 |
| | iv | B3-T4 | 24.00 | 11.30 | 12.70 | BL2 |
| | Sub-total "B3" | 117.60 | 54.60 | 63.00 | | |
| 4 | i | B4-T1 | 25.30 | 14.20 | 11.10 | B |
| | ii | B4-T2 | 12.00 | 10.40 | 1.60 | B |
| | iii | B4-T3 | 66.00 | 38.70 | 27.30 | B |
| | iv | B4-T4 | 56.30 | 47.40 | 8.90 | B |
| | Sub-total "B4" | 159.60 | 110.70 | 48.90 | | |
| 5 | i | B5-T1 | 14.00 | 14.00 | 0.00 | B |

| | | | | | | |
|----|-----------------|--------------|--------|--------|-------|-----|
| | ii | B5-T2 | 10.20 | 9.50 | 0.70 | B |
| | iii | B5-T3 | 7.70 | 5.80 | 1.90 | B |
| | iv | B5-T4 (BL2) | 79.70 | 53.80 | 25.90 | BL2 |
| | Sub-total "B5" | | 111.60 | 83.10 | 28.50 | |
| 6 | i | B6-T1 | 36.30 | 33.30 | 3.00 | B |
| | ii | B6-T2 | 9.20 | 7.00 | 2.20 | B |
| | iii | B6-T3 | 5.10 | 4.10 | 1.00 | B |
| | iv | BL3 | 28.00 | 23.90 | 4.10 | B |
| | v | B6-T4 | 9.30 | 8.60 | 0.70 | B |
| | vi | B6-T5 (BL4) | 47.20 | 43.20 | 4.00 | BL4 |
| | vii | BL5 | 33.30 | 5.80 | 27.50 | BL4 |
| | Sub-total "B6" | | 168.40 | 125.90 | 42.50 | |
| 7 | i | B7-T1 | 32.00 | 30.20 | 1.80 | B |
| | ii | B7-T2 | 12.20 | 11.80 | 0.40 | B |
| | iii | B7-T3 | 50.40 | 47.40 | 3.00 | B |
| | Sub-total "B7" | | 94.60 | 89.40 | 5.20 | |
| 8 | i | B8-T1 | 30.50 | 30.50 | 0.00 | BL4 |
| | ii | B8-T2 | 28.90 | 28.90 | 0.00 | BL4 |
| | iii | B8-T3 | 13.00 | 13.00 | 0.00 | BL4 |
| | iv | BL5 | 16.90 | 16.90 | 0.00 | BL5 |
| | v | B8-T4 | 37.20 | 37.20 | 0.00 | BL4 |
| | Sub-total "B8" | | 126.50 | 126.50 | 0.00 | |
| 9 | i | B9-T1 | 23.10 | 21.80 | 1.30 | BL4 |
| | ii | B9-T2 | 42.80 | 39.80 | 3.00 | BL4 |
| | iii | B9-T3 | 31.40 | 30.30 | 1.10 | BL4 |
| | Sub-total "B9" | | 97.30 | 91.90 | 5.40 | |
| 10 | i | B10-T1 | 43.00 | 31.30 | 11.70 | BL4 |
| | ii | B10-T2 | 27.00 | 20.50 | 6.50 | BL4 |
| | iii | B10-T3 | 35.60 | 28.30 | 7.30 | BL4 |
| | Sub-total "B10" | | 105.60 | 80.10 | 25.50 | |
| 11 | i | B11-T1 | 3.80 | 3.70 | 0.10 | BL6 |
| | ii | B11-T2 | 67.50 | 65.70 | 1.80 | BL6 |
| | iii | B11-T3 | 47.20 | 45.50 | 1.70 | BL6 |
| | iv | B11-T4 | 13.50 | 12.40 | 1.10 | BL6 |
| | v | B11-T5 | 11.90 | 11.50 | 0.40 | BL6 |
| | Sub-total "B11" | | 143.90 | 138.80 | 5.10 | |
| 12 | i | B12-T1 (BL6) | 13.50 | 12.90 | 0.60 | BL6 |
| | ii | B12-T2 (BL6) | 33.70 | 32.20 | 1.50 | BL6 |
| | iii | B12-T3 (BL6) | 21.30 | 20.50 | 0.80 | CL6 |
| | iv | B12-T4 (BL7) | 14.30 | 13.40 | 0.90 | CL6 |
| | v | B12-T5 (BL7) | 19.00 | 18.50 | 0.50 | CL7 |
| | Sub-total "B12" | | 101.80 | 97.50 | 4.30 | |

| | | | | | | |
|----|-----------------|--------------|--------|--------|-------|------|
| 13 | i | B13-T1 | 23.90 | 22.30 | 1.60 | CL7 |
| | ii | B13-T2 | 17.70 | 16.80 | 0.90 | CL7 |
| | Sub-total "B13" | | 41.60 | 39.10 | 2.50 | |
| 14 | i | B14-T1 | 38.20 | 37.80 | 0.40 | B |
| | ii | B14-T2 | 26.90 | 25.50 | 1.40 | B |
| | iii | B14-T3 | 8.40 | 7.80 | 0.60 | B |
| | iv | B14-T4 | 6.80 | 6.60 | 0.20 | BL8 |
| | v | B14-O1 & O2 | 4.80 | 4.60 | 0.20 | B |
| | Sub-total "B14" | | 85.10 | 82.30 | 2.80 | |
| 15 | i | B15-T1 (BL8) | 34.50 | 29.90 | 4.60 | BL8 |
| | ii | B15-T2 (BL8) | 17.30 | 16.50 | 0.80 | BL8 |
| | iii | B15-T3 (BL8) | 26.00 | 19.90 | 6.10 | BL8 |
| | iv | B15-T4 (BL8) | 18.10 | 15.10 | 3.00 | BL8 |
| | v | B15-T5 (BL8) | 11.70 | 10.30 | 1.40 | BL8 |
| | vi | B15-T6 (BL8) | 19.70 | 16.40 | 3.30 | BL8 |
| | Sub-total "B15" | | 127.30 | 108.10 | 19.20 | |
| 16 | i | B16-T1 | 30.70 | 27.90 | 2.80 | B |
| | ii | B16-T2 | 30.00 | 21.50 | 8.50 | B |
| | iii | B16-T3 | 15.80 | 12.10 | 3.70 | B |
| | iv | B16-T4 | 49.40 | 36.90 | 12.50 | B |
| | v | B16-T5 | 42.90 | 12.00 | 30.90 | B |
| | Sub-total "B16" | | 168.80 | 110.40 | 58.40 | |
| 17 | i | B17-T1 | 10.90 | 7.70 | 3.20 | B |
| | ii | B17-T2 | 17.90 | 14.90 | 3.00 | B |
| | iii | B17-T3 | 13.30 | 10.40 | 2.90 | B |
| | iv | B17-T4 | 17.80 | 15.00 | 2.80 | B |
| | v | B17-T5 | 26.60 | 23.00 | 3.60 | B |
| | Sub-total "B17" | | 86.50 | 71.00 | 15.50 | |
| 18 | i | B18-T1 | 5.80 | 5.00 | 0.80 | B |
| | ii | B18-T2 | 21.30 | 18.80 | 2.50 | BL9 |
| | iii | B18-T3 | 35.20 | 25.20 | 10.00 | BL10 |
| | iv | B18-O1 | 14.50 | 12.80 | 1.70 | BL11 |
| | v | B18-T4 | 29.10 | 26.70 | 2.40 | BL12 |
| | vi | B18-T5 | 29.50 | 24.70 | 4.80 | BL13 |
| | vii | B18-T6 | 29.30 | 0.00 | 29.30 | BL14 |
| | viii | T | 73.90 | 73.90 | 0.00 | BL15 |
| | Sub-total "B18" | | 238.60 | 187.10 | 51.50 | |
| 19 | i | B19-T1 | 31.40 | 17.40 | 14.00 | B |
| | ii | B19-T2 | 28.40 | 23.70 | 4.70 | B |
| | iii | B19-T3 | 47.10 | 25.40 | 21.70 | B |
| | iv | B19-T4 | 22.30 | 22.30 | 0.00 | B |
| | Sub-total "B19" | | 129.20 | 88.80 | 40.40 | |

| | | | | | | |
|-----------------------|-----------------|-------------|---------|--------|--------|-----|
| 20 | i | B20-O1 | 17.30 | 1.00 | 16.30 | B |
| | ii | B20-O2 | 18.10 | 10.80 | 7.30 | B |
| | iii | B20-O3 | 19.60 | 11.60 | 8.00 | B |
| | Sub-total "B20" | | 55.00 | 23.40 | 31.60 | |
| Sub Total of B-System | | 2488.90 | 1929.70 | 559.20 | | |
| 1 | i | C1-T1 | 38.30 | 25.70 | 12.60 | C |
| | ii | C1-T2 | 32.50 | 26.70 | 5.80 | C |
| | iii | C1-T3 | 14.20 | 1.20 | 13.00 | C |
| | iv | C1-T4 | 5.40 | 0.50 | 4.90 | C |
| | v | C1-T5 | 12.70 | 0.00 | 12.70 | C |
| | vi | C1-T6 | 13.60 | 0.00 | 13.60 | C |
| | Sub-total "C1" | | 116.70 | 54.10 | 62.60 | |
| 2 | i | C2-T1 | 51.20 | 51.20 | 0.00 | CL1 |
| | ii | C2-T2 | 64.30 | 64.30 | 0.00 | CL1 |
| | Sub-total "C2" | | 115.50 | 115.50 | 0.00 | |
| 3 | i | C5-T1 | 11.50 | 11.00 | 0.50 | C |
| | ii | C5-T2 | 5.70 | 5.50 | 0.20 | C |
| | iii | C5-T3 | 4.50 | 4.20 | 0.30 | C |
| | iv | C5-T4 | 29.50 | 26.80 | 2.70 | C |
| | v | T | 129.20 | 129.20 | 0.00 | C |
| | Sub-total "C5" | | 180.40 | 176.70 | 3.70 | |
| 4 | i | C6-T1 (CL7) | 17.00 | 17.00 | 0.00 | CL7 |
| | ii | C6-T2 (CL7) | 19.80 | 19.80 | 0.00 | CL7 |
| | Sub-total "C6" | | 36.80 | 36.80 | 0.00 | |
| 5 | i | C7-O1 (CL7) | 18.90 | 18.90 | 0.00 | CL7 |
| | ii | C7-O2 (CL7) | 10.50 | 10.50 | 0.00 | CL7 |
| | iii | C7-O3 (CL7) | 23.20 | 22.10 | 1.10 | CL7 |
| | Sub-total "C7" | | 52.60 | 51.50 | 1.10 | |
| 6 | i | C8-T1 (CL7) | 11.90 | 11.90 | 0.00 | CL7 |
| | ii | C8-T2 (CL7) | 14.20 | 12.30 | 1.90 | CL7 |
| | iii | C8-T3 (CL7) | 25.90 | 21.20 | 4.70 | CL7 |
| | iv | C8-T4 (CL7) | 16.60 | 13.20 | 3.40 | CL7 |
| | v | C8-T5 (CL7) | 32.00 | 15.10 | 16.90 | CL7 |
| | vi | C8-T6 (CL7) | 69.90 | 66.50 | 3.40 | CL7 |
| | vii | C8-T | 29.60 | 29.10 | 0.50 | CL7 |
| | Sub-total "C8" | | 200.10 | 169.30 | 30.80 | |
| 7 | i | C9-T1 (CL4) | 126.70 | 0.00 | 126.70 | CL1 |
| | ii | C9-T2 | 57.70 | 22.60 | 35.10 | CL1 |
| | iii | C9-T3 | 19.70 | 10.90 | 8.80 | CL1 |
| | Sub-total "C9" | | 204.10 | 33.50 | 170.60 | |
| 8 | i | C10-T1 | 22.70 | 18.20 | 4.50 | CL1 |

| | | | | | | |
|-----------------------|-----------------|--------------|---------|---------|---------|-----|
| | ii | C10-T2 | 4.50 | 4.10 | 0.40 | CL1 |
| | iii | C10-T3 | 14.50 | 7.70 | 6.80 | CL1 |
| | iv | C10-T4 (CL5) | 82.40 | 8.00 | 74.40 | CL5 |
| | Sub-total "C10" | | 124.10 | 38.00 | 86.10 | |
| 9 | i | C11-T1 (CL5) | 140.00 | 1.50 | 138.50 | CL1 |
| | ii | C11-T2 | 9.60 | 3.20 | 6.40 | CL1 |
| | iii | C11-T3 | 13.70 | 12.60 | 1.10 | CL1 |
| | iv | C11-T4 | 6.30 | 6.20 | 0.10 | CL1 |
| | Sub-total "C11" | | 169.60 | 23.50 | 146.10 | |
| 10 | i | C12-T1 | 90.80 | 90.80 | 0.00 | CL1 |
| | ii | C12-T2 | 30.50 | 29.50 | 1.00 | CL1 |
| | iii | C12-T3 | 14.50 | 13.70 | 0.80 | CL1 |
| | Sub-total "C12" | | 135.80 | 134.00 | 1.80 | |
| 11 | i | C13-T1 | 43.60 | 18.10 | 25.50 | CL6 |
| | ii | C13-T2 | 59.80 | 26.30 | 33.50 | CL6 |
| | iii | C13-T3 | 41.50 | 4.00 | 37.50 | CL6 |
| | iv | C13-T4 | 46.50 | 20.90 | 25.60 | CL6 |
| | Sub-total "C13" | | 191.40 | 69.30 | 122.10 | |
| 12 | i | C14-T1 | 13.30 | 0.00 | 13.30 | CL1 |
| | ii | C14-T2 | 19.30 | 0.00 | 19.30 | CL1 |
| | iii | C14-T3 | 38.70 | 0.00 | 38.70 | CL1 |
| | iv | C14-T4 | 64.80 | 0.00 | 64.80 | CL1 |
| | Sub-total "C14" | | 136.10 | 0.00 | 136.10 | |
| 13 | i | C15-T1 | 62.20 | 48.90 | 13.30 | CL1 |
| | ii | C15-T2 | 33.00 | 25.50 | 7.50 | CL1 |
| | Sub-total "C15" | | 95.20 | 74.40 | 20.80 | |
| Total | | | 1758.40 | 976.60 | 781.80 | |
| 14 | i | C3 & C4 | 375.15 | 375.15 | 0.00 | |
| | ii | CL2 | 128.80 | 0.00 | 128.80 | |
| | Sub-total | | 503.95 | 375.15 | 128.80 | |
| Sub Total of C-System | | | 2262.35 | 1351.75 | 910.60 | |
| Grand Total (B+C) | | | 4751.25 | 3281.45 | 1469.80 | |

Source: Narayani Lift-Khageri Management Division Office, Bharatpur

System Operation and Cost of Electricity

As for operation, the project office is in charge of intake up to the main canal, and the total operating expenses for the system in the year 2020 are Rs 9,659,018.00 out of which Rs 5,159,018.00 for staff expenses and Rs 4,500,000.00 for electricity.

Government Budget for Operation and Maintenance

Total Staffs working for System operation is Pump Operator

(3 people), Electric Lineman (2 people), Mechanical Helper (2 people), Watchman (4 people) and Seasonal Helper (5 people) per month (during pump operation). This information is illustrated in Table 10.

From Table 10, the graph, it was observed that in recent years the cost incurred in electricity of the system is decreasing and hence, operation cost per hectare is decreasing. As Nepal is moving forward to the electricity self-independent, the operation days of the pump can be increased so that fields receive more water see Figure 5.

Table 10. Expenses of Narayani Lift Irrigation System of Past 8 Years

| S.No | Fiscal Year | Operation and Maintenance Cost NRS | Electricity Bill NRS | Total Cost (Excluding Staff Expenses) NRS | Pump Operation Days/ year | Operation & Maintenance Cost/ ha |
|------|-------------|------------------------------------|----------------------|---|---------------------------|----------------------------------|
| 1 | 2068/69 | 40596188.00 | 2,67,80,000.00 | 38046188.00 | 98 | 8543.00 |
| 2 | 2069/70 | 5,159,018.00 | 45,00,000.00 | 9,659,018.00 | 93 | 2,032.73 |
| 3 | 2070/71 | 9,030,227.50 | 60,00,000.00 | 15,030,227.50 | 98 | 3,163.09 |
| 4 | 2071/72 | 9,370,245.00 | 1,15,00,000.00 | 20,870,245.00 | 107 | 4,392.12 |
| 5 | 2072/73 | 17,496,621.00 | 1,00,00,000.00 | 27,496,621.00 | 97 | 5,786.63 |
| 6 | 2073/74 | 8,263,328.02 | 1,60,70,000.00 | 24,333,328.02 | 90 | 5,120.92 |
| 7 | 2074/75 | 9,308,137.71 | 2,77,32,460.19 | 37,040,597.90 | 90 | 7,795.15 |
| 8 | 2075/76 | 2,465,364.69 | 1,25,00,000.00 | 14,965,364.69 | 90 | 3,149.44 |
| 9 | 2076/77 | 5,799,577.70 | 20,00,000.00 | 7,799,577.70 | 90 | 1,641.41 |




Figure 5. Budget Status of NLIS

Also, it is found that, there is huge gap between the water tariff collected per hectare from the operation cost per hectare and the difference in budget is sanctioned by the Ministry of Energy, Water resources and Irrigation. (MOE, 2076).

Water User Tariff Collection

The basis for collection of service charges from farmers is the charge on irrigation area. The secondary and tertiary canal is maintained by the user's association. The farmer's necessity for effective water distribution among themselves was the motive, and the associations have been formed getting advice from the project office.

The major activity of the association is to remove settled soil and clean canals, and materials like concrete and gravel are provided by the project office in case of need. The state of maintenance depends, but it is still low level on the whole.

An irrigation fee of 221 Rs/Ha is imposed on beneficiary

farmers by the users association, but the tariff collection is not satisfactory for most rejects to pay. According to (Bhatta, Matsuoka, & Shrestha, Vol.14/No.1), The reason is supposed that many farmers have not got enough water as they expected, as in some other projects the fee is paid to a certain extent.

It is not that farmers don't pay the tax, during the survey it is found that every farmer pays the water user tariff but the majority of farmers i.e 55% of farmer pay only when they are reminded and the minority of them i.e 17% usually forgets to pay the tariff and there were 28% of them who regularly pays water user tariff on time.

It is found that maximum farmers are willing to pay when reminded. Both the local farmers and water user association were interviewed for are farmers comfortable with the tariff that they have to pay. The result of study is as below:

Majority of members of water user association i.e 40%,

say that farmer are fully comfortable on the water user’s tariff but on same context only 17.5% agreed. Majority of the farmers’i.e 37.5% agreed that they are paying only because of compulsion only, 33.33% of members of WUA agreedwith this context. While member of WUA doesn’t think that farmers are not willing to pay tariff and it is found that 20% of the farmer doesn’t will to pay tariff. Also, a balanced population of farmer and member (i.e 25% of farmer and 26% of member of WUA) agreed that people are not comfortable on water tariff (Figure 6).

Water Users Association

Narayani Lift Irrigation is a joint managed system in which, Narayani lift-Khageri Management Division under the Department of Irrigation as an agency is managing and

separate organizational structure of Water User Association is functioning.

For the proper management of Narayani Lift Irrigation System in an effective and well-coordinated manner, a Narayani lift irrigation water users association (NLIWUA) has been formed as per the Water Resource Act 2049 comprising 23 members in 2051 BS. This central committee, chaired by Mr. PurnaBahadurRanabhat has been working for the system. Further, 2 branch committees comprising 47 members, 35 sub branch committees with 315 members, 1 constituent assembly committee with 105 members and 12 regional members have been directly involved in smooth sailing and functioning of NLIS. An outline of the existing organizational structure of WUA of NLIS is presented in Table 11.




Figure 6. Status of Farmers and Member of WUA on comfort for water tariff

Table 11. Outline of the existing organizational structure of WUA of NLIS

| Types of Committee | Number of committee | Number of member |
|--------------------------------|---------------------|------------------|
| Central committee | 1 | 23 |
| Branch committee | 2 | 47 |
| Sub-branch committee | 35 | 315(35*9) |
| Constituent Assembly Committee | 1 | 105(35*3) |
| Regional member | | 12 |

Source: Narayani Lift Irrigation Water User Association

The NLIWUA has been collecting water tariff with users regularly. The WUA used to collect Rs.100/Ha/Year since 2051 BS(KC, M, &Gautam, DR (2006)):International Water Management Institute.(2004). But from the fiscal year 2057/58, the collection amount has increased to Rs.150/Ha/Year. Now, the collection amount has increased to Rs.221/Ha/Year.

Roles of Water User's Association

In Joint management irrigation system, Water User's Association is the main executive body for the management of system. There are various roles of WUA in proper management of system. The main roles of Narayani Lift Irrigation water users association (NLIWUA) are as follows :

1. Reliable delivery of water after pump operation.
2. Clear decision making and taking account of user's interest.
3. Dispute Management.
4. Maintenance of secondary and tertiary canal.
5. To aware farmers for proper use of system.

6. Call for regular meetings for management and maintenance of system.

To understand how the user's and government officials find the roles played for NLIWUA a study was done and all the government officials finds the roles of water user's association is very effective and the response of local people is presented in Figure 7.

During the study, majority of the local farmers' i.e 58% find the role played by NLIWUA is effective and 17% agreed that it is very effective. While 20% of them said somehow effective role had been played, there are 5% according to whom the role played is not effective similar to Kattel, S. (2007).

The general study of the roles played by the WUA is not sufficient for the overall study of roles played by the WUA. Hence, to understand the roles played by the Water User association in detail, the Relative Importance Index is also applied. The result of the Relative Importance Index is as in Table 12:




Figure 7. Effectiveness on Roles played by NLIWUA

Table 12. Ranking of Roles Played by NLIWUA

| S. No. | Roles | Local Farmers | | Member of WUA | | Average Importance | |
|--------|---|---------------|-----------------|---------------|-----------------|--------------------|-----------------|
| | | RII (in %) | Rank | RII (in %) | Rank | RII (in %) | Rank |
| a. | Reliable delivery of water after pump operation. | 65 | 5 th | 82.67 | 3 rd | 75.6 | 3 rd |
| b. | Clear decision making and taking account of user's interest. | 68.5 | 3 rd | 76 | 4 th | 73 | 4 th |
| c. | Dispute Management. | 73 | 2 nd | 92 | 1 st | 84.4 | 2 nd |
| d. | Maintenance of secondary and tertiary canal. | 85 | 1 st | 90.67 | 2 nd | 88.4 | 1 st |
| e. | To aware farmers for proper use of system. | 54 | 6 th | 59 | 6 th | 62.4 | 6 th |
| f. | Call for regular meetings for management and maintenance of system. | 69 | 4 nd | 68 | 5 th | 68.4 | 5 th |

The result of RII based on the roles played by the NLIWUA giving preference 60% to the response of members of WUA and 40% to views of local farmers shows that NLIWUA played its role very satisfactory in the maintenance of the secondary and tertiary canal. Also, more emphasis should be given to aware the farmer for proper use of the system, since the role played to aware the farmers were not satisfactory. More awareness plans and campaigns should be launched by the WUA to motivate and educate the locals to use the water system.

Dispute Management

A dispute is very common in the jointly managed irrigation system. There are certain rules and regulations to manage these disputes. Since disputes are very common, therefore, the resolution mechanism must be strong enough so that it does not get converted into conflict. Hence, dispute management is a must which needs to be utilized in the full phase. It is one of the most important roles that NLIWUA is playing. The NLIWUA is responsible for dispute management

within the system. To understand the status of the dispute during the use of water from the system, the study was done whose result is presented in Figure 8.

During the study it was found that about 42.5% of respondents agreed that always dispute is encountered during the use of water in Main Canal B, similarly, 20% of respondents agreed on always dispute is encountered during the use of water in Main Canal C. In both canals, very few said that there is no dispute, i.e 2.5% of the respondent of Main canal B and 6.67% of them of Main canal C. 32.5% of them of main canal B and 46.67% of them of the Main canal C agreed there is dispute frequently encountered.

Causes of Dispute

There may be many more causes of the dispute based on geography and nature of the system, there are some the dispute noted in the system during the study and a Relative Importance Index Analysis is done (Figure 9).




Figure 8. Frequency of Dispute in Main Canal




Figure 9. RII on Causes of Disputes

Awareness, Trainings and Meetings

One of the main roles of WUA is to organize different campaigns to aware the farmers' proper use of water and the conservation of canals and other components such as gates. Similar pieces of training and meetings are organized so that there is easier management of the system.

During the study, it was found that the participation of 48% of the farmers in the meeting and training is very less whereas 32% take part frequently and 17% of farmers are regular attendees. Also, 3% of the farmers have never taken part in the meeting and the training that had been organized by the WUA.

Opinion and Importance of NLIS

The most important awareness about the project among the farmers as observed during the study period is the value of irrigation water without which their income level decreased by 50%.

It is known that by using the water from the system beneficiaries highly benefited. During the study it is found that 100% of government officials consider the system as only secondary source and the result of views of local farmers and members of WUA on opinion about the system is shown in Figure 8.

27.5% of local farmers and 33.33% of members of WUA find the system very beneficial similarly 52.2% of the farmers, 46.67% of member of WUA and 100% government officials find NLIS as secondary source. For 12.5% farmers and 13.33% member of WUA they found system partially beneficial. There were 7.5 % of the farmers and 6.67% of the member of WUA who doesn't find NLIS beneficial (Figure 10).

Agricultural Benefits

The Narayani Lift Irrigation Systems through management of existing irrigation system, expansion of irrigated area and expansion of year round irrigation area can enhance the agricultural benefits as stated below.

- Reliable irrigation water supply increase crop yields and subsequent increase in production and farm income.
- Water supply can initiate crop diversification with more cash crops with high return value like vegetable, fruits, cash crops etc.
- Potential for high value agricultural commodities based markets are available as Bharatpur is the entry point to Pokhara and Kathmandu where there are ever increasing demands.
- All the command areas of canal are accessible with road, so transportation of agricultural products could be brought to market easily.
- The command area is very fertile and mildly sloping towards south-west direction. If the farmers could be motivated for crop diversification, this area is suitable for upland crops and of conventional irrigation practice of farrow, graded irrigation practice could be implemented.

The response of farmers and member of WUA on agricultural status after the Narayani lift irrigation system comes on operation. 30% of famers and 13.33% of member of WUA says, agricultural status is increased rapidly and also 2.5% of farmer and 6.67 % member of WUA deny this and say agricultural status is decreased than that of before. 22.5% farmer and 20 % of member of WUA say the agricultural status is same as before.




Figure 10. Opinions on NLIS




Figure 10. Opinions on NLIS

45% of the farmers and 60% of the member of WUA agree that they are more motivated on agriculture as the system comes in operation.

Socio-Economic Benefit

By the operation of system, it is found that more farmers are motivated on agriculture then it is sure that this will upgrade the socio-economic condition of the overall area. Though most of the area is urban significant involvement of women is there, not only in urban area but in village area also women are engaged in system management.

Not only the involvement of women the economic condition of the farmers are also changed than that of before. Result of study on economic status of society after the system is presented Figure 11.

Wide variety of respondents i.e 45% of farmers and 53.33% of the member of WUA agree on economic status is improving slowly. And 22.5% of farmers and 13.33% of member of WUA agree that the economic status of the society is upgrading. 30% of local farmers and 26.67% of member of WUA says the economic status of society is same as before. And minority of farmers i.e 2.5% and member of WUA i.e 6.67% says the economic status is degrading.

Irrigation Parameters

Effective Rainfall

The 60% of monthly rainfall, which exceeds 100 mm/month, was counted as effective rainfall. The site data was the average monthly rainfall at Rampur Agricultural Station (See table 13).

Table 13. Effective Rainfall data

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Rainfall (mm/day) | 0 | 0 | 0 | 0 | 0 | 6 | 7 | 7 | 3 | 0 | 0 | 0 |

Table 14. Peak Water Requirement

| Crop | Peak Water Requirement (Liter / Sec / ha) | Period |
|----------------|---|---------------------|
| Rice (normal) | 1.2 | September |
| Rice (early) | 1.8 | April |
| Wheat | 0.5 | June – February |
| Corn | 0.5 | May |
| Mustard | 0.45 | November – December |
| Mung Bean | 0.7 | May |
| Vegetables | 0.9 | April |
| Grass (Fodder) | 1.7 | May |

Water Requirement

The peak water requirement of each crop is shown in table 14. Based on these figures, the peak water requirement for Narayani Scheme was estimated at 2.00 liter per sec per Ha.

Generally the water of the system is used to irrigate the land in which rice, wheat and vegetable are grown. The following Table 15, shows the water requirement up to a crop growing stage. (liter / sec / Ha.)

Table 15. Water requirement upto a crop growing stage. (liter / sec / Ha.)

| Growth Stage (%) | Rice | Wheat | Vegetables |
|------------------|------|-------|------------|
| 0 | 1.05 | 0.30 | 0.10 |
| 10 | 1.05 | 0.30 | 0.22 |
| 20 | 1.10 | 0.50 | 0.40 |
| 30 | 1.15 | 0.73 | 0.53 |
| 40 | 1.25 | 0.93 | 0.59 |
| 50 | 1.33 | 1.00 | 0.61 |
| 60 | 1.40 | 0.95 | 0.59 |
| 70 | 1.45 | 0.78 | 0.54 |
| 80 | 1.45 | 0.54 | 0.45 |
| 90 | 1.40 | 0.32 | 0.35 |
| 100 | 1.30 | 0.22 | 0.31 |

Data in the Tables 13 and 14 are derived from the Statistical Information on Nepalese Agriculture (2075/ 76).

Here, the effective rain cannot solely fulfill the water requirement of the crops in the field around the command area. Hence, to increase the water availability to the crop the peak water requirement for Narayani Scheme was estimated at 2.00 liter per sec per Ha.

Irrigation Efficiency

Irrigation efficiency is a percentage of retained water in an effective soil layer against the total volume of intake water. It is calculated by the conveyance efficiency (CE) multiplied by the application efficiency (AE), and they are defined as follows:

$CE (\%) = 100 - \text{volume of conveyance loss} / \text{volume of intake water}$

$AE (\%) = 100 - \text{volume of application loss} / \text{volume of inlet water}$

Where;

Conveyance Loss: evaporation and/or leakage loss during conveyance

Application loss: surface run-off and / or percolation out of the effective layer after inlet to a field. The irrigation efficiency according to crops is shown in Table 16.

Table 16. Irrigation Efficiency

| | Rice | dry-season crops |
|----------------------------|------|------------------|
| Conveyance efficiency (%) | 80 | 80 |
| Application efficiency (%) | 90 | 60 |
| Irrigation efficiency (%) | 72 | 48 |

Problem and Threats of Narayani Lift Irrigation System

Frequent Damage of Electro-Mechanical Components

The electromechanical components which are too old and the accessories are not easily available in the local market.

High Sediment in Water/ Sediment Management

NLIS usually pump water during monsoon season having high sediment content in the river, whereas during winter and spring season low water level of the Narayani river causes extreme vibration of the pumps as such pumping of water can not be continued. So pumping during the monsoon season has caused sediment problems in the canal system, inlet channel, and also damages the pump parts frequently. Previous studies on the sedimentation issues of NLIS indicated that the gabion dam in front of the inlet channel should be improved to abstract skimmed top water level of Narayani River, monitoring its concentration regularly, and pumping operation should be restricted during flood period. In addition, the lowest conduit of the gabion dam should be closed during monsoon season; neither of the above recommendations is generally followed. In order to address these problems sediment control measures should be adopted at the entry point to minimize the influx of higher order sediments, and a sediment basin provision at the link canal for removing substantial sediments probably larger than 0.06 mm size particles. The present note will explore the possible solutions for such measures and will recommend appropriate solution. Suspended sediment concentration in the river varies largely due to geological phenomenon occurring in its catchment; it varies from 8000 -15000 mg/l in common and might go up to 30000 mg/l during high flood. The hydrological station No. 450 of DHM has some data on sediment content of the river and its discharge variations. The previous studies have found some relationship of the sediment concentration. It has indicated that the average sediment concentration during June to August months varies from 1894 to 6000 mg/l as shown in Table 17.

It is certain that the sediment concentrations in the Narayani River are very high during July and August. Therefore, the gabion dam should be made as filter block to check the high concentrated sediment influx into the system.

Table 17. Mean Monthly Discharge and Sediment Concentration of Narayani River

| Mean Data of the years 2010 to 2020 | June | July | August |
|--|------|------|--------|
| Mean Monthly discharge m ³ /sec | 1548 | 3576 | 4231 |
| Mean Sediment Concentration mg/l | 1894 | 5007 | 5978 |

Source: Narayani Lift-Khageri Management Division Office, Bharatpur

It is learnt that the system is designed for 6000 ppm concentration of sediment, however during monsoon season it varies from 2000 to 30,000 ppm, which cause frequent breakdown of the impeller blades and other accessories of the pumps at A.

Urbanization and Reduction of Irrigation Area

The existing irrigation system is located nearby Bharatpur Metropolitan city where there is regular influx of migrated population so that the urban areas are increasing by construction of physical infrastructures like buildings, roads, and others. By which there is reduced the irrigation command area. The total area under the NLIS designed irrigation is found to be reduced from the 2488.90 to 2267.90Ha among the canal "B" and 2262.35 to 944.075Ha in "C" system. The systems which will have agriculture practices in next 10 to 15 years are assumed approximately to be 2000 Ha in B System and 600 Ha in C-System.

Water Leakage from Canals

The NLIS is suffering from high leakage of the irrigation water from the main canal. Only two km length of canal B system from the beginning (especially urban area) is masonry lining and some for few other sections partly to prevent the seepage losses. About 3.5 km length of main

canal C is lined and the branch canal CL-1 is lined within the urban area. The loss due to seepage in earthen channels is much more than loss by evaporation. The percentage loss in earthen canal is 15 to 20%, transit loss is 2.5%, evaporation losses is 1.5 to 2.0% of seepage loss, loss in cultivation over field 8 to 9%(Indian Practical Civil Engineer's Handbook 17/72, 2005). Based on the data, leakage assessment is shown in Table 18.

Change in Agriculture Pattern

Difference in farming program between original plan and actual situation most of farmers choose only paddy as a monsoon crop.

Over Loading in Some Tertiary Canals

In the cause there has been growing demand for outlet directly from a reliable canal, the total water management come to be quite complicated, and some quarrel arise among farmers on water distribution. Table 19, shows the percentage of land getting full irrigation water in the project.

Generally, the pump operation time is during the sowing period of rice which is mid monsoon and early winter, as field also experiences rainfall during that period and tertiary canal is verysmall and sometime due to rainfall and water from system, overloading of tertiary is seen and due to such overloading, bursting of tertiary is observed.

Regular Maintenance and Question of Sustainability

WUA and beneficiary farmers need to made more responsibility in regular maintenance of the system. The user farmers will also be made responsive in paying regular water tariff. It is conceptualized to be responsible for local ownership and longer run sustainability of the lift irrigation system. Relative Importance index for Problem and Threats of the System shown in Table 20.

Table 18. Leakage Assessment

| Main Canal | Peak Demand (m ³ /sec) | Supply (m ³ /sec) | Supply of Irrigation Water through lined and unlined canal | | | | | Net Irrigation Supply |
|------------|-----------------------------------|------------------------------|--|--------------------|--|-----------------------|------------|-----------------------|
| | | | Supply | Seepage Loss @ 20% | Loss in cultivation over fields @ 8.5% | Evaporation Loss @ 2% | Total Loss | |
| B | 4.54 | 6.20 | 6.20 | 1.24 | 0.53 | 0.12 | 1.89 | 4.31 |
| C | 1.89 | 0.80 | 0.79 | 0.16 | 0.07 | 0.02 | 0.24 | 0.55 |

Table 19. Percentage of Land Getting Full Irrigation Water in the Project

| Canal | Spring | Monsoon | Winter |
|------------|--------|---------|--------|
| "B" System | 0.00 % | 68.06 % | 5.00 % |
| "C" System | 0.00% | 42.83% | 2.50% |

Table 20.RII on Problems and Threats of NLIS

| S. No. | Factors | Local Level | | Member of WUA | | Governmental Officials | | Average Importance | |
|--------|--|-------------|-----------------|---------------|-----------------|------------------------|-----------------|--------------------|-----------------|
| | | RII | Rank | RII | Rank | RII | Rank | RII | Rank |
| A | Frequent Damage of Electro-Mechanical Components | 59.333 | 3 rd | 76.2 | 2 nd | 58.22 | 3 rd | 63.947 | 3 rd |
| B | High Sediment in Water/ Sediment Management | 78.333 | 1 st | 83.6 | 1 st | 86.4 | 1 st | 83.139 | 1 st |
| C | Urbanization and Reduction of Irrigation Area | 60.333 | 2 nd | 71.6 | 3 rd | 73.06 | 2 nd | 68.803 | 2 nd |
| D | Water leakage from canals | 33.667 | 6 th | 59.8 | 5 th | 42 | 4 th | 44.838 | 4 th |
| E | Change in Agriculture Pattern | 40 | 5 th | 62.2 | 4 th | 32.4 | 5 th | 43.62 | 5 th |
| F | Over loading in some tertiary canals | 56.667 | 4 th | 33.6 | 7 th | 30.5 | 6 th | 39.281 | 6 th |
| G | Regular Maintenance and Question of Sustainability | 20 | 7 th | 42.2 | 6 th | 22.56 | 7 th | 27.684 | 7 th |

In this RII analysis, giving 40% preference to response of Governmental officials, 30% to response of members of WUA and 30% to views of local farmers, it is found that, Sedimentation Management is principle threat of the system. Similarly, urbanization and reduction in command area is also the threat that system has to care. Frequent damage in the components is also one of the problem and updated components should be replaced. In study water leakage is not found in high scale. This seems that, concerned authority has been doing well for maintenance, but also maintenance is a problem and should be mitigated as possible. Proper Agriculture pattern should be set and overloading of tertiary should be mitigated.

Conclusions

From the study, following conclusions are made:

The roles of NLIWUA was found to be effective, and among the different roles, NLIWUA was seen very satisfactory in Maintenance of the secondary and tertiary canal. Each year before the pump operation time maintenance work is completed.

The role of NLIWUA was found to be not satisfactory to organize meetings and aware farmers to use the system effectively. Though meetings were called very less, only 17% of farmers regularly attended the meetings.

Dispute during the water distribution time was frequently observed and role of NLIWUA was effective in dispute management. The main reason for dispute i.e 77.3% of

cases of dispute was found due to lack of co-ordination among the farmers regarding water allocation. Since, very less farmers attend meetings and frequently awareness and meeting was not organized this may have happened.

After the system came in operation changes were observed in socio-economic and agricultural status of the users. Women Participation in public/social works had increased, increase in economic status by 45% is noted also 55.4 % of farmers had been motivated in agriculture and shift of farmers from rice plantation to cash crop.

The water user tariff collected (Rs.221/Ha) was used only to maintain the canal. The operational cost and maintenance cost of components of pump house was allocated by Government. The budget allocated was sufficient only for temporary maintenance but system is in need of proper rehabilitation. Due to temporary repair and maintenance efficiency of the system is reduced.

Narayani Lift Irrigation System was operated around 3 to 4 months in a year and majority farmers i.e 57.5% said the water was sufficient only for one crop, hence 52.5% of farmers consider NLIS as secondary source. During the remaining 8 to 9 months majority of farmers depend on ground water sources like tube well, as well as rain water.

To provide sufficient water round the year, any kind of secondary sources should be connected to the system. In this context, 60% government officials 59.3 % Member of WUA and 74% of farmers agreed. As the tail end of this

system was on Khageri System, command area of Khageri System could also be increased and irrigation status of West Chitwan would be improved.

Among the pumps in system (i.e 5 nos in Pump house A and 4 nos in Pump house B) without frequent maintenance no pump would be in operating condition. Also one pump was completely damaged and was not operating completely. Due to this, cost of the system was increasing and on other hand water pumping volume was decreasing. Although due to rapid urbanization the command area was decreasing and with decreased water volume system was performing satisfactory.

Sediment Management was principle threat to the system. Due to silting in intake, pumps are also damaged and require frequent maintenance and decreased efficiency of pumps is noted along with increase in cost was found. Sand deposit of up to 1m in Link canal and around 0.6m in main canals, up to 0.3m in secondary and tertiary canals were found. In some places, blockage of tertiary due to sand deposits was also found.

Bharatpur Metropolitan City being a developing city in country, unplanned urbanization was rapid and due to this the command area of NLIS was continuously decreasing. The designed command area was 4700 Ha in study year command area reduced to 3282 Ha. Reduction of 1469 Ha was found.

Water leakage assessment was done based on (Indian Practical Civil Engineer's Handbook 17/72, 2005), and found that, to the demand of 6.3 m³/sec, supply of 7 m³/sec was done and total loss of 2.13 m³/sec was found and which results net irrigation of 4.87 m³/sec.

Length of Main Canal 'B' is 17.681 km with 2.5km concrete lining and in many places lining work is going on, and rest is wet masonry. Length of Main Canal 'C' is 10.2 km with 3.5km concrete lining and rest is wet masonry. Length of secondary canal is 15.5 km and all are wet masonry lining. Tertiary canal is earth canal with brick masonry in inlet points.

Recommendations

According to the results and discussion of the study, we can recommend that:

This seems, the water intake from source is insufficient for farmers, so it is recommended to add the water to intake. As, 52.5% of farmers, 40% of the member of WUA and 60% of governmental officials suggest it is most necessary of secondary source to increase abundance of water in system. Detailed Feasibility Study to add secondary source is highly recommended.

Replacement of the old worn pumps by new ones to improve performance as old pumps is beyond economic repair.

Proper rehabilitation plan for the pump house is needed so that water supply would be increased with decreased budget for operation and maintenance.

Proper Urban Planning norms and directives should be adopted by the metropolitan city or government in order to balance and check the transformation of agricultural land to urban area. Due to unplanned and rapid urbanization service to downstream level are effected.

Either the services of irrigation system should be increased or water user tariff should be updated, since many farmers don't will to pay water user tariff. Hence new method of tariff collection could be introduced to address the condition of both NLIWUA and farmers.

Sediment Management is main problem of the system hence improvement should be done. The improvement works has to be defined in two sections; one should be around gabion dam or on the river front of the intake channel to prevent the entry of high sediment from river, second to settle the pumped sediment content in the link canal by providing settling basin with hydraulic flushing arrangement towards the river back.

Acknowledgement

We are thankful to Er. Ravi Ghimire (Project Co-ordinator), Er. Manjil Thapaliya (External Examiner), Er. Gyanendra Bhandari (Head of Department, Civil Engineering), Er. Bhim Bhandari (BE Program Co-ordinator), Er. Hari Bhandari (Principal) and Oxford Engineering and Management College Family.

We wish to extend gratitude to helpful and coordinating staffs of Narayani Lift Khageri Management Division, Bharatpur; Er. Khem Bahadur Pathak, Senior Divisional Engineer, NLKMD; Er. Kul Raj Chalise, Engineer, NLKMD; Purna Bahadur Ranabhat, President, Narayani Lift Irrigation Water User's Association; Hari Prasad Bhattarai, Secretary, NLIWUA for their support during data collection and valuable suggestion to complete our project.

References

1. Acharya M, Poudel R, Bhandari B. Comparative Performance Study of Farmers Managed and Agency Managed Irrigation System in Chitwan. IAAS Reserch Report 1993/94; 178-185.
2. APROSC & JMA. Nepal Agriculture Prespective Plan : Final Report. Kathmandu: Agriculture Project Service Center 1995.
3. Bhatta KP, Sharma R, Ishida A. Performance of agency - managed and farmer - managed irrigation system . Irrigation and Drainage 2005; 177-191.
4. Development MO. (2075/2076). Statistical Information on Nepalese Agriculture. Kathmandu: Government of Nepal.

5. District Development Committee. (2072). District Profile Chitwan. District Profile ,Chitwan.
6. Gajurel K, KC, TB. Relative stress on Community Managed Irrigation System in Chitwan, Nepal. Fourth Annual Common Property Conference. Manila, Philippines: Irrigation Management System Study Group 2003.
7. Gautam KR, Pande PR, Paudel RC et al. Pre Feasibility Study Report of Mid hill Lift Irrigation Project. Kathmandu, Nepal: Department Of Irrigation.
8. Government of Nepal, L. (n.d.). Local Mapping Resource Project.
9. International Water Management Institute. (2004). Farmer Managed Irrigation System in Chitwan Valley of Nepal. Workshop in Political Theory and Policy Analysis. Bloomington: Indiana University.
10. KCM, Gautam DR. Promoting Good Governance of Water User Association in Nepal. Guideline for Good Governance 2006.
11. Kattel S. Dispute Management in FMIS : A Case Study of Geya Danda Irrigation System 2007.
12. Metrology DO. (2075). River Profile of Mahabharat Range. Ministry of Energy, Water Resource and Irrigation.
13. Narayani Lift. Khageri Irrigation Management Office, Ministry of Physical Infrastructure Development 2021. com.np/study-of-maintenance-requirements-and-system-upgrading-of-narayani-lift-irrigation-system-pumping-station-a/
14. Ministry of Energy (MOE), Water Resources and Irrigation. (2076). Irrigation Annual Budget. Kathmandu: Government of Nepal.
15. Mishra AK, Aithal PS, Performance Assessment of Irrigation: A Case from Nepal-Asia. *International Journal of Management, Technology, and Social Sciences (IJMSTS)* 2022; 7(1): 444-464. DOI: <https://doi.org/10.5281/zenodo.6657541>
16. Mishra AK. Evaluate the Farmers' Participation for Irrigation Development in Nepal. *International Social Mentality and Researcher Thinkers Journal* 2022; 8(57): 630-644.
17. Dahal AK, Mishra AK, Aithal PS. Operation of Design Review in Small Irrigation Projects in Dang Valley of Nepal. *International Journal of Case Studies in Business, IT and Education (IJCSBE)* 2022; 6(1): 139-157.
18. Dahal AK, Mishra AK, Aithal PS. Factors Affecting Design Review: A Case from Dang Valley, Nepal-Asia. *International journal of applied engineering and management letters (IJAEML)* 2022; 6(1): 160-175. <https://doi.org/10.5281/zenodo.6350839>.
19. Mishra AK, Dahal AK. Effects of Design Review of Selected Irrigation Projects from Dang Valley, Nepal-Asia. *African Journal of Applied Research* 2022; 8(1): 39-62. <http://www.ajaronline.comhttp://doi.org/10.26437/ajar.03.2022.3>.
20. Mishra AK, Yadav P, Aithal PS. Dispute of the Contracts: A Case from Sikta Irrigation Project, Banke, Nepal. *International Journal of Case Studies in Business, IT, and Education (IJCSBE)* 2021; 5(1): 169-185. DOI: <http://doi.org/10.5281/zenodo.5037030>
21. Mishra AK, Yadav P, Aithal PS. Time and Cost Performance Status of Sikta Irrigation Contract. *International Journal of Management, Technology, and Social Sciences (IJMSTS)* 2021; 6(1): 286-305. DOI: <https://doi.org/10.5281/zenodo.5081379>.
22. Mishra AK, Yadav P, Aithal PS. Time and Cost Performance Status of Sikta Irrigation Contract. *Empirical Economics Letters*, 20 (Special Issue 3) 2021: 9-30. DOI: <https://doi.org/10.5281/zenodo.6538088>. <http://www.eel.my100megs.com/volume-20-number-july-3-special-issue.htm>
23. Poudel KP, Sharma S. Small Irrigation System in Nepal. *Jawalakhel Lalitpur: Nepal GIS Society* 2012.
24. Pradhan P. A Comparative Study of 21 Farmer Managed Irrigation System in Nepal. *Pattern of Irrigation System in Nepal* 2000; 140-162.
25. Rijal E, Khatri E, Kharel E. Irrigation Engineering. Kathmandu: GL Book House 2018.
26. Sharma KR. Joint Management and Turnover Program : A case study of Agency Managed Irrigation System in Nepal. Workshop in Political Theory and Policy Analysis. Bloomington: International Association for the Study of Common Property.
27. Singh M, Liebrand J, Joshi D. Cultivating Success and Failure in policy : Participatory Irrigation In Nepal. *Development in Practice*.
28. Statistical Year Book of Nepal. Central Bureau of Statistics 2003.
29. CBS, 2011. opendatanepal.com/organization/central-bureau-of-statistics?tags=census